

LISTING OF CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

sub C1
B1
1 (presently amended): A reflector lamp comprising a glass shell, a base, a wire lamp, and a heat shield, said wire lamp being disposed within said glass shell, said glass shell having a concave inner surface and an outer surface, said glass shell having a thickness, said glass shell having a reflective coating disposed on said inner surface, said glass shell having a bottom, said glass shell having an opening at said bottom, said base extending from said bottom of said glass shell, said opening and said base defining a nose chamber, said heat shield being disposed substantially within or adjacent said nose chamber, said nose chamber having an exhaust hole adapted for the passage of an exhaust tube therethrough in a base of said nose chamber, said ~~exhaust hole being substantially offset from the center of said base of~~ said nose chamber having a diameter of less than 1 inch.

2 (original): A reflector lamp according to claim 1, wherein said concave inner surface is substantially parabolic.

3 (original): A reflector lamp according to claim 2, wherein said heat shield is positioned so as to substantially complete said parabolic inner surface.

4 (original): A reflector lamp according to claim 1, wherein said heat shield is a concave curved-shape.

5 (original): A reflector lamp according to claim 1, wherein said heat shield comprises stainless steel.

6 (original): A reflector lamp according to claim 1, wherein said heat shield comprises a substrate and a reflective coating disposed on said substrate.

7 (previously amended): A reflector lamp according to claim 1, wherein said nose chamber has a plurality of holes disposed in said base of said nose chamber.

8 (original): A reflector lamp according to claim 7, wherein the number of said holes is three.

9 (previously amended): A reflector lamp according to claim 8, wherein two of said holes are adapted for the passage of ferrules therethrough, and one of said holes is said exhaust hole.

10 (presently amended): A reflector lamp according to claim 1, ~~said nose chamber having a diameter of less than 1 inch~~ wherein said hole adapted for passage therethrough of said exhaust tube is substantially offset from the center of said base of said nose chamber.

11 (original): A reflector lamp according to claim 6, wherein said reflective coating on said substrate comprises at least one metal selected from the group consisting of silver, gold, white gold, aluminum, and chromium.

12 (original): A reflector lamp according to claim 6, wherein said substrate comprises stainless steel.

Cont
C1
13 (original): A reflector lamp according to claim 3, wherein said heat shield is positioned above said opening at said bottom of said glass shell within 4 mm thereof.

B1
cont
14 (original): A reflector lamp according to claim 3, wherein said heat shield is positioned below said opening at said bottom of said glass shell within 4 mm thereof.

15 (presently amended): A reflector lamp comprising a glass shell, a base, and a wire lamp, said wire lamp being disposed within said shell, said glass shell having a concave inner surface and an outer surface, said glass shell having a reflective coating disposed on said inner surface, said glass shell having a bottom, said glass shell having an opening at said bottom forming the top of a slot in said base, said opening having a major diameter and a minor diameter, said major diameter being substantially longer than said minor diameter, said minor dimension being less than one inch, said wire lamp extending into said slot.

16 (previously amended): A reflector lamp according to claim 15, wherein said base has three openings therein, said openings being in communication with said slot in said base.

17 (original): A reflector lamp as in claim 15, wherein said slot has a substantially rectangular cross-section.

18 (original): A reflector lamp as in claim 15, wherein

said slot has a substantially elliptical cross-section.

19 (original): A reflector lamp according to claim 15, wherein said base of said lamp has a substantially cross-shaped cross-section.

20 (presently amended): A reflector lamp comprising a glass shell, a wire lamp, and a flange, said wire lamp being disposed within said glass shell, said glass shell having a concave inner surface and an outer surface, said glass shell having a reflective coating disposed on said concave inner surface, said flange extending from said outer surface of said glass shell and defining a perimeter of a chamber, an inwardly extending annular overhang portion of said glass shell extending over said chamber and being substantially continuous with said glass shell, said overhang portion having an inner surface coated with said reflective coating, said overhang portion having an opening therethrough in communication with said chamber, said chamber having a diameter of less than one inch.

21 (previously amended): A reflector lamp according to claim 20, further comprising a glass cup attached to said flange extending from said outer surface of said glass shell, said glass cup comprising a base, a wall extending from said base of said glass cup at a perimeter thereof, and a plurality of openings extending through said base of said glass cup providing fluid connectivity between inner and outer surfaces thereof.

22 (original): A reflector lamp according to claim 20,

wherein said flange is integrally formed as part of said glass shell.

*Could
C1*
23 (previously added): A reflector lamp according to claim 6, said reflective coating on said substrate comprising chromium.

*B1
comel.*
24 (previously added): A reflector lamp according to claim 15, said major diameter being longer than said minor diameter by a factor selected from the group consisting of 1.5, 2, 3, 4, and 5.

25 (previously added): A reflector lamp according to claim 15, said major diameter being 4 times longer than said minor diameter.

26 (previously added): A reflector lamp according to claim 21, said wall of said glass cup and said flange extending from said glass shell having substantially the same diameter, said wall of said glass cup being permanently attached to said extending flange by glass fritting.